

Quotation Notes:

Quotation (Includes Tax): _____

Date: _____

Color: _____

Install .032 Seamless Gutter: _____

Install .019 2" x 3" Downs: _____

Install .024 3" x 4" Downs: _____

Hand Fitted Corners: _____

Remove & Haul Old Material: _____

Install Leaf Protection: _____

Install Hinges: _____

Ask about our Lifetime Gutter System Guarantee!

Why Choose Tomlinson-Cannon?

DECADES OF LOYAL SERVICE

Serving our Customers Since 1948
Dedicated & Highly Skilled Employees
Best Products & Installation Methods
LIFETIME GUARANTEES
Most Jobs Completed In One Day
We Install Year-Round, Including Winter
Bank Financing Available
Discover, Mastercard & Visa Accepted

CALL US TODAY!

Other Services

Mudjacking

We will re-level and restore driveways, patios, sidewalks, garage floors or any concrete slab at the half of the cost of new.

Basement Waterproofing

Our drain tile system or crack injections are guaranteed to dry up your wet basement.

Basement Wall Anchoring

If your basement walls are cracked or bowed, our "Grip-Tite" anchor system is guaranteed to solve the problem quickly and simply without excavation or disturbing outside concrete and landscapes.

Grip-Tite
MANUFACTURING CO.

A
AEROSAW, INC.
CONCRETE SAWING & CORE DRILLING

Tomlinson
Cannon

Tomlinson Cannon

GUTTERS

Custom Fitted

Heavy Duty Seamless Aluminum
Gutters & Downspouts



**Call Us Today for a
Prompt, Free Quote!**

Iowa City (Main): 319-774-3422

Cedar Rapids: 319-774-3422

Davenport: 563-362-3237

Waterloo: 319-409-6850

tomlinson-cannon.com

Why are quality gutters so important?

Worn, leaking or improperly installed gutters or downspouts may cause:

- Rotting Overhangs (soffit & fascia)
- Damage to Siding
- Basement Water Leaks & Bowing Walls
- Damage to Exterior Landscapes
- Heaving & Cracking Sidewalks

What else should you know about us?

- LIFETIME Maintenance Free Gutter Guarantee
- LIFETIME LeafProof Guarantee to End Gutter Cleaning Permanently
- The aluminum is non-corrosive and the finish is baked on enamel: white, linen, almond, cream, antique ivory, wicker, clay, gray, terratone, rosewood, brown, musket brown, black, Grecian green and special colors.

Tomlinson-Cannon est. 1948	Others
<h3>1. Gutter Thickness</h3>	
 <p>.032</p> <ul style="list-style-type: none"> • strongest available, capable of bearing heavy loads of ice, snow, water and ladders • LIFETIME GUARANTEE 	 <p>.027</p> <ul style="list-style-type: none"> • weak, unstable, may not be able to rest a ladder against it safely
<h3>2. Corners</h3>	
 <ul style="list-style-type: none"> • attractive, hand-fitted with one seam • much stronger (.032) • Guaranteed never to leak 	 <ul style="list-style-type: none"> • unsightly with 3 seams • much weaker (.019) • Prone to Leak
<h3>3. Gutter Installation</h3>	
 <p>Hidden Bracket Installation</p> <ul style="list-style-type: none"> • concealed for an attractive gutter • screwed on or anchored into truss (every 24") so it can't work loose • gutter behind drip edge 	 <p>Spike and Ferrule Installation</p> <ul style="list-style-type: none"> • visible because it's pounded through outside of gutter • will work loose in short period of time • gutter is often on top of drip edge 
<h3>4. Outlets</h3>	
 <ul style="list-style-type: none"> • separate unit • pop-rivet or snap in • 33% more water released • no taper, less clogging 	 <ul style="list-style-type: none"> • a hole punched out of gutter • weak, downspout could pull loose • gutter could tear or leak • or outlet is tapered
<h3>5. Downspout Installation</h3>	
 <ul style="list-style-type: none"> • large downs = .024 thickness • .032 down holders • Stainless steel screws 	 <ul style="list-style-type: none"> • large downs = .019 thickness • .019 down holder • screws will rust
<h3>6. Leaf Guards (Optional)</h3>	
 <p>screen</p>  <p>Leaf Proof</p> <ul style="list-style-type: none"> • screen is heavy aluminum and removable • LeafProof — end gutter cleaning permanently 	 <p>Steel</p>  <p>Plastic</p> <ul style="list-style-type: none"> • steel rusts & reacts to aluminum • plastic or roll-out aluminum collapses