

GUTTERS

Custom Fitted

Heavy Duty Seamless Aluminum
Gutters & Downspouts



Why are quality gutters so important?

Worn, leaking, or improperly installed gutters or downspouts may cause:

- Rotting overhangs (soffits & fascia)
- Damage to siding
- Basement water leaks & bowing walls
- Damage to exterior landscapes
- Heaving & cracking sidewalks

What else should you know about us?

- Year-round installs and repairs
- Many choices in color and style
- We offer affordable and quick response gutter cleaning on any system
- We repair and replace roofs, soffit and fascia - save with a bundle discount!

Why choose Tomlinson Cannon?

Decades of Loyal Service

- Serving our customers since 1948
- Dedicated & highly skilled employees
- Best products & installation methods
- Lifetime guarantee the system will not leak
- Warranty work is our priority

Tomlinson Cannon est. 1948		The Other Guys	
1. Gutter Thickness			
 <p>.032</p>	<ul style="list-style-type: none">• Thickest gutters available for durability against ice, snow, water, and ladders	 <p>.027</p>	<ul style="list-style-type: none">• Weak, unstable, may not be able to rest a ladder against it safely
2. Corners			
	<ul style="list-style-type: none">• Attractive, hand-fitted with one seam• Much stronger (.032)• Guaranteed never to leak		<ul style="list-style-type: none">• Unsightly with 3 seams• Much weaker (0.19)• Prone to leak
3. Gutter Installation			
 <p>Hidden Bracket Installation</p>	<ul style="list-style-type: none">• Concealed for an attractive gutter• Screwed on or anchored into truss (every 24") so it can't work loose• Gutter behind drip edge 	 <p>Spike and Ferrule Installation</p>	<ul style="list-style-type: none">• Visible because it's pounded through outside of gutter• Will work loose in short period of time• Gutter is often on top of drip edge 
4. Outlets			
	<ul style="list-style-type: none">• Separate unit• Pop-rivet or snap in• 33% more water released• No taper, less clogging		<ul style="list-style-type: none">• A hole punched out of gutter• Weak, downspout could pull loose• Gutter could tear or leak• Outlet is tapered
5. Downspout Installation			
	<ul style="list-style-type: none">• Large downs = .024 thickness• .024 down holders• Stainless steel screws		<ul style="list-style-type: none">• Large downs = .019 thickness• .019 down holder• Screws will rust

Call Us Today for a Prompt, Free Quote!

Iowa City (Main): 319-337-2225 | Cedar Rapids: 319-362-1747 | Davenport: 563-326-2418 | Waterloo: 319-234-1223

✉ info@tomlinson-cannon.com | 🌐 tomlinson-cannon.com